


## High Fibre Count Duct dielectric optical mini Flextube® cable

### Cable Design

IEC/EN 60794



- not to scale -

**Micro-module:** Thin wall tubing (FlexTube®), filled with a suitable compound, housing the single-mode optical fibres.

**Water tightness:** dry core with swellable elements.

**Protection / reinforcement yarns.**

**Strength members:** glass fibre reinforced plastic material.

**Outer Sheath:** PE. Ripcord(s) underneath the sheath.

This High Fibre Count mini Flextube dielectric optical cable is designed for outdoor installation in duct by pulling, jetting or floating technics. Mainly used for distribution and access network. The Flextube® design provides easier storage & faster installation. Finger access to the fibres : no specific tools to open the Flextube.

### Technical data

# Fibres (grouped by 12) *	≤	360	432	576	720	864
Module - Ø	mm			1.3		
Cable Diameter	mm	14.5	15.2	16.7	18	19.2
Cable Weight	kg / km	145	160	190	220	250
Max installation tension	daN	230	250	300	350	400
Min. bending radius	mm	Without Tension 10 x Cable-Ø		Under Maximum Tension 20 x Cable-Ø		
Temperature range	°C	Installation -5 -> +40;		Transport. & Storage -40 -> +70 ;	Operation -30 -> +60	

\* other configuration upon specific request

Please refer to our General Installation, Safety & Handling recommendations before handling.

### Main characteristics

Test	Standard	Valeur	Sanction*
Maximum Tension at installation (short term)	IEC 60794-1-2-E1	see table above	$\Delta\alpha$ reversible
Crush	IEC 60794-1-2-E3	150 daN / 100mm	$\Delta\alpha \leq 0.1$ dB
Impact	IEC 60794-1-2-E4	5 Nm, 3 impacts, r=300mm	$\Delta\alpha$ reversible
Torsion	IEC 60794-1-2-E7	1m, +- 180°	$\Delta\alpha \leq 0.1$ dB
Cable bend	IEC 60794-1-2-E11	R = 10 x cable Ø	$\Delta\alpha$ reversible
Temperature range	IEC 60794-1-2-F1	-30 -> +60°C	$\Delta\alpha \leq 0.1$ dB /km
Water Penetration	IEC 60794-1-2-F5B	sample=3m, water=1m	No water leakage after 24 hour

\* values for single-mode fibres, all optical measurements performed at 1550 nm

### Optical Characteristics

See the attached cabled optical fibre data sheet.

## Identification

### Fibre Colours

No.	1	2	3	4	5	6	7	8	9	10	11	12
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	black	aqua	pink

### Flextube Colours

No.	1	2	3	4	4	5	7	8	9	10	11	12
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	Light green	aqua	pink
No.	12	14	15	16	17	18	19	20	21	22	23	24
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	Light green	aqua	pink
No.	25	26	27	28	29	30	31	32	33	34	35	36
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	Light green	aqua	pink
No.	37	38	39	40	41	42	43	44	45	46	47	48
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	Light green	aqua	pink
No.	49	50	51	52	53	54	55	56	57	58	59	60
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	Light green	aqua	pink
No.	61	62	63	64	65	66	67	68	69	70	71	72
Colour	red	blue	green	yellow	violet	white	orange	grey	brown	Light green	aqua	pink

### Sheath Colour:

The outer sheath colour is black.

### Sheath Marking:

The outer sheath is marked in 1 meter intervals as follows:

**<Manufacturer> <year of manufacture> OPTICAL CABLE <optional: product type> <nb and type of fibre> <length marking in meter>**

## Logistic

### Packing:

Wooden drums with protection.

### Delivery Lengths:

Standard delivery length is 2 km with a tolerance of - 1% / + 3%

© PrysmianGroup 2012, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by PrysmianGroup: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of PrysmianGroup. The information is believed to be correct at the time of issue. PrysmianGroup reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by PrysmianGroup.