



OFDC-B8

Outdoor fiber distribution closure

EnLighten
FTTH Solutions

The gel sealed outdoor distribution closure is used to break out fibers from a looped cable to connect business customers, MDU's or single living units.

The closure can be used as well in aerial, pedestal and underground (up to 2 meters) environment.

The gel, used for both, closure and cable seals, allows easy access and is fully re-useable.

Features

- Single ended design
- Compact enclosure (163 x 326 x 102 mm)
- Gel block with spring loading for the cable seal
- Not required to cut loop-through fiber of the feeding cable
- Organizer can be removed from closure body
- Compatible with RECORDsplice, SMOUV and ANT splice protectors
- Transient free customer provisioning
- Drop cables are terminated individually
- Separate storage of un-connected fibers from spliced drop fibers
- Possibility to integrate PON splitters
- Main cable up to 18 mm diameter
Drop cable up to 6 mm diameter
- Easy drop cable termination on strain relief device.

Kit content

- Box with fiber organizer
- Main cable seal and termination device
- Drop cable seal for 8 drops with drop cable termination devices
- Universal splice holder for 12 splices

Xpres version

OFDC-B8-XX / X - X - XX

X1 Xpress-drop UPC
X2 Xpress-drop APC 8°

Number of adapters in case of Xpresdrop (2, 4 or 8)

U Universal splice holder (12 splices RECORDsplice & SMOUV or a combination)

NN no splitter
14 1:4 splitter
18 1:8 splitter
1G 1:16 splitter

ISROD version

OFDC-B8-X - X - XX - X

U12 Splice tray with universal holder for 12 splices

Number of trays (1 or 2)

NN no splitter
14 1:4 splitter
18 1:8 splitter
1G 1:16 splitter

Number of ISROD included (2, 4 or 8)

Adapters

OC-ADP-X1-X1-NNCS-(24) XPRESS-DROP UPC (MOQ = 24 pcs)
 OC-ADP-X2-X2-NNCS-(24) XPRESS-DROP APC 8° (MOQ = 24 pcs)

Ordering example

24 x OC-ADP-X1-X1-NNCS-(24) 1 bag with 24 pcs

Tyco Electronics, TE logo, RECORDsplice and SMOUV are trademarks.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, Tyco Electronics makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Tyco Electronics' obligations shall only be as set forth in Tyco Electronics' Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem NV
 Diestsesteenweg 692
 3010 Kessel-Lo, Belgium
 Tel 32-16 351 011 (USA)1-919-557-8900
 Fax 32-16 351 697 (USA)1-919-557-8498
 www.tycoelectronics.com
 www.telecomosp.com
 TC 1045/DS/1 02/08